

Trelleborg Road Tape



Product Information

Trelleborg Removable Road Tapes solve your temporary marking problem.

Extremely durable for quality marking and ease of removal without surface marring.

Removable Road Tapes consist of a durable and flexible rubber composite layer with a polyurethane coating. A pressure sensitive adhesive gives a strong bond to asphalt and concrete surfaces and the tape is covered with functional particles to provide very

durable performance. We manufacture under ISO 9001 and ISO14001 procedures to ensure consistency. White and yellow tapes have lot number information imprinted under the adhesive layer to provide lot traceability.

Installation conditions.

- Air- and surface temperature above 10 degrees Celsius and rising.
- A completely dry surface free of oils, dust, loose particles, sand, dirt and other forms of contamination.



Photos front page and page 2 Plastiline Tolochenaz



Standard Removable

Trelleborg Removable Road Tape is a bright idea for temporary traffic deviations and delineation through road works and construction sites.

- High visibility guides motorists safely through construction zones.
- Highly retro reflective at night.
- Excellent daytime visibility.
- Good skid resistance even in wet conditions.

Trelleborg Primer, when used in addition to the tape, will enhance durability and ease of removal.

Colours: White, yellow and orange.
Special colours on request.

Standard dimensions:

- 10 cm x 100m
- 12 cm x 100 m
- 15 cm x 100 m
- 20 cm x 100 m

Other widths are available on request.

Wide materials also available with release liner.



All Tape is produced in our own factory in Trelleborg, Sweden.

Masking Tape

Trelleborg Removable Masking Tape is ideal for masking lane lines, edge lines, crossovers, and counter flows common to road works, construction sites and temporary traffic deviations.

- Easy applied over existing markings.
- Eliminates expensive, time-consuming mechanical removal of permanent lane markings and damage to the road surface.

- Quickly and easily removed intact or in long sections without damage to permanent road marking underneath.
- High skid resistance

Standard dimensions:

- 15 cm x 100 m
- 22 cm x 50 m

Other widths are available on request. Wide materials also available with release liner.



Contacts



Road Tape
Trelleborg Industri AB, S-231 81 Trelleborg, Sweden
Phone: + 46 410-510 00 Fax: +46 410 511 22 E-mail: roadtape@trelleborg.com
www.trelleborg.com/roadtape